

## TEKNISKA SPECIFIKATIONER

Batterihylla med autmatsäkring för att ansluta batterier till batteribackup.

Battery shelf 24V M har kapacitet för två 45 Ah batterier.

Battery shelf 24V L har kapacitet för två 150 Ah batterier.

Battery shelf floor har kapacitet för fyra 150 Ah batterier.

Battery shelf L har kapacitet för fyra 150 Ah batterier.

Det går att koppla max 4 batterihyllor till en batteribackup.

EN54 24V 15A 1U med fyra Battery shelf 24V L



## TEKNISKA DATA

Tekniska data	Artikelnummer	E-nummer	Produktbeskrivning
Battery shelf 24V M	BS010000024BM01	5213578	Batterihylla med plats för två 45 Ah batterier. Färdiga kablar till batterierna samt färdig kabel för anslutning till batteribackup (1U/2U). Produkten skall monteras i rack.
Battery shelf 24V L	BS020000024BL01	5213587	Batterihylla med plats för två 150 Ah batterier. Färdiga kablar till batterierna samt färdig kabel för anslutning till batteribackup (1U/2U). Produkten skall monteras i rack.
Battery shelf floor	BS030000000BF01	5213510	Batterihylla för golv. Får plats på golvet mellan stolparna på i ett 19" rackskåp.
Battery Shelf L	BS020000000BL01	5213624	

	Battery shelf 24V M	Battery shelf 24V L	Battery shelf floor	Battery Shelf L
Mått	215x438x200mm (5HE)	Mått:290x490x430mm (7HE)	130x448x500mm(3HE)	290 x 490 x 430 mm (7HE)
Vikt	7 kg	10 kg	5 kg	5 kg

	Battery shelf 24V M	Battery shelf 24V L	Battery shelf floor	Battery Shelf L
Batterier som får plats på hyllan	2 st 28 Ah eller 2 st 45 Ah	2 st 75 Ah eller 2 st 100 Ah eller 2 st 120 Ah eller 2 st 150 Ah	2 st 75 Ah eller 2 st 100 Ah eller 2 st 120 Ah eller 2 st 150Ah eller 4 st 62 Ah eller 4 st 92Aheller 4 st 100Ah eller 4 st 125Aheller 4 st 150 Ah FT	2 st 150Ah eller 4 st 150 Ah FT
Material	Pulverlackad plåt			
Färg	Svart			

Tekniska data	
Rekommenderad miljö	Miljöklass 1, Inomhus, 20% ~ 90% relativ fuktighet
Produkterna möter kraven enligt	EMC Directive 2014/30EU, Low Voltage directive: 2014/35/EU CE directive according to 765/2008, Emission: EN61000-6-:2001, EN55022:1998--A1:2000, A2:2003 Klass B, EN61000-3-2:2001. Immunity: EN61000-6-2:2005, EN61000-4-2, -3, 4, -5, -6, -11.
Garanti	2 år
Tillverkare	Milleteknik AB
Ursprungsland	Sverige

Detta dokument kan ändras utan föregående meddelande.

Alla uppgifter publiceras med reservation för tryckfel

## TECHNICAL SPECIFICATIONS

Battery shelf with automatic fuse for connecting batteries to battery backup.

Battery shelf 24V M has capacity for two 45 Ah batteries.

Battery shelf 24V L has capacity for two 150 Ah batteries.

Battery shelf floor has capacity for four 150 Ah batteries.

Battery shelf L has capacity for four 150 Ah batteries.

It is possible to connect a maximum of 4 battery shelves to a battery backup.

EN54 24V 15A 1U with four Battery shelf 24V L



## TECHNICAL DATA

Technical data	Item number	Email number	Product description
Battery shelf 24V M	BS010000024BM01	5213578	Battery shelf with space for two 45 Ah batteries. Cables for the batteries and cable for connection to battery backup (1U/2U). The product must be mounted in a rack.
Battery shelf 24V L	BS020000024BL01	5213587	Battery shelf with space for two 150 Ah batteries. Cables for the batteries and cable for connection to battery backup (1U/2U). The product must be mounted in a rack.
Battery shelf floor	BS030000000BF01	5213510	Battery shelf for floor. Fits on the floor between the posts in a 19" rack cabinet.
Battery Shelf L	BS020000000BL01	5213624	

	Battery shelf 24V M	Battery shelf 24V L	Battery shelf floor	Battery Shelf L
Measure	215x438x200mm (5U)	Dimensions: 290x490x430mm (7HE)	130x448x500mm(3HE)	290 x 490 x 430 mm (7U)
Weight	7 kg	10 kg	5 kg	5 kg
Batteries that fit on the shelf	2 pcs 28 Ah or 2 pcs 45 Ah	2 pcs 75 Ah or 2 pcs 100 Ah or 2 pcs 120 Ah or 2 pcs 150 Ah	2 pcs 75 Ah or 2 pcs 100 Ah or 2 pcs 120 Ah or 2 pcs 150Ah or 4 pcs 62 Ah or 4 pc 92Aheller 4 pcs 100Ah or 4 pcs 125 Aheller 4 pcs 150 Ah FT	2 pcs 150Ah or 4 pcs 150 Ah FT

	Battery shelf 24V M	Battery shelf 24V L	Battery shelf floor	Battery Shelf L
Material	Powder coated sheet metal			
Color	Black			

Technical data	
Recommended environment	Environmental class 1, Indoor, 20% ~ 90% relative humidity
The products meet the requirements according to	EMC Directive 2014/30EU, Low Voltage directive: 2014/35/EU CE directive according to 765/2008, Emission: EN61000-6-2:2001, EN55022:1998:-A1:2000, A2:2003 Class B, EN61000-3-2:2001. Immunity: EN61000-6-2:2005, EN61000-4-2, -3, 4, -5, -6, -11.
Guarantee	2 years
Manufacturer	Milleteknik AB
Country of origin	Sweden

This document is subject to change without notice.

All information is published subject to errors